

## Outdoor Non-absorbent

### CITITM

#### Category Information

Vinyl loops scrape dirt and moisture off shoes, allowing it to fall in to the mat and not be tracked in to the building.

Durable flexible material is ultra violet resistant, performs well in different climates and adapts to any surface.

Does not absorb water.

Choice of backed or unbacked construction:

Backed version ensures minimum movement and keeps debris away from the floor in indoor areas. Backing is a non-porous vinyl layer which is cured into the upper web for maximum non-delaminating durability.

Unbacked version allows dirt and water to flow through in outdoor areas.

Slip resistance tested R11 according to DIN51130 and BRG181.

#### Cleaning Tip:

Vacuum clean or wash off with a hose.

### 273 CITITM 16 mm backed

#### Specifications:

- Thick coils (strand diameter 1 mm) of extruded from 100% PVC.
- Backing: vinyl.
- Overall thickness: 16 mm.
- Weight: 6 kg per m<sup>2</sup>.
- Fire retardancy ASTM D2859 passes DOC FF 1-70, DIN EN 13501 B6-S1.

#### Recommended use:

- Suitable for heavy traffic conditions.
- For placement interior facility entrances or recessed wells.

#### Full roll:

- 120 cm x 18 meter
- 120 cm x 6 meter

#### Custom lengths:

- 120 cm per linear meter



16 mm

### 274 CITITM 14 mm unbacked

#### Specifications:

- Thick coils (strand diameter 1 mm) of extruded from 100% PVC.
- Overall thickness: 14 mm.
- Weight: 4.8 kg per m<sup>2</sup>.
- Fire retardancy ASTM D2859 passes DOC FF 1-70, DIN EN 13501 B6-S1.

#### Recommended use:

- Suitable for heavy traffic conditions.
- For placement exterior facility entrances or recessed wells.

#### Full rolls:

- 120 cm x 18,3 meter
- 120 cm x 6 meter

#### Custom lengths:

- 120 cm per linear meter



14 mm

### 271 CITITM 10 mm backed

#### Specifications:

- Fine coils (strand diameter 0.35 mm) of extruded from 100% PVC.
- Backing: vinyl.
- Overall thickness: 10 mm.
- Weight: 3 kg per m<sup>2</sup>.
- Fire retardancy ASTM D2859 passes DOC FF 1-70, DIN EN 13501 B6-S1.

#### Recommended use:

- Suitable for light to medium traffic conditions.
- For placement interior facility entrances or recessed wells.

#### Full rolls:

- 120 cm x 18 meter
- 120 cm x 6 meter



10 mm

www.notrax.com

## Spaghetti

Anthracite Green Brown

Grey Black Navy Blue

Red

Product testing

Water Cracks Dust

Water Cracks Dust

Water Cracks Dust

Gold Brown Green

Blue Grey Anthracite

Product testing

Water Cracks Dust

Water Cracks Dust

Water Cracks Dust

www.notrax.com