

Indoor Absorbent

113 MASTER TRAX™

Category Information

Durable carpet flooring, designed for large indoor entrance areas, including wall-to-wall applications. Offers many possibilities for creative combinations that will allow the entrance become part of the complete interior design.

Unsurpassed ability to retain moisture and scrape debris from foot traffic while maintaining its great looking appearance for the longest time.

Mold and mildew resistant, UV stabilized, crush resistant and remains unaffected by climate extremes.



Synthetic rubber backing

Recommended use:

- Suitable for even the heaviest of traffic conditions.
- For placement inside entrances or outside if not exposed to rain.
- In recess frames (depth 10 mm) or wall to wall installations in shopping malls, airports, hospitals, hotel lobbies, banks, restaurants, golf facilities (spikes resistant), fitness centres, elevators, locker rooms, ski lodges, skating rinks, automobile showrooms, any public or professional building.

Cleaning Tip:

Vacuum/shampooing or use extraction method to clean.



Special colours: Full rolls 200 cm x 21 m



Specifications:

- Nibbed resin punched carpet consisting of anti-static 100% polypropylene fibres.
- Easy to install, can be cut to any size or shape without edge ravel.
- 1700 grams of yarn per m².
- Backing: synthetic rubber (rolls), bitumen (tiles)
- Overall thickness: 11 mm.
- Weight: 3,2 kg per m².
- Fire retardancy: ASTM D2859 passes DOC-FF-1-70, Rostest norm NPБ244-97, CCPБNLOP-019 B01723.

www.notrax.com

Full rolls:

- 200 cm x 21 meter

Custom lengths:

- 200 cm per linear meter

Tiles:

- 50 cm x 50 cm
- Bitumen backing
- Stock colours: Charcoal

www.notrax.com

Contract

